

10/522,090

S.N.
5/4/07

By Express Mail # EL997184658US · January 21, 2005

Fig. figure 6 shows is a cross ~~section~~ sectional view through a fourth exemplary embodiment of an interference suppression device in the region of a short shielding arm,

Fig. figure 7 shows is a cross ~~section~~ sectional view through the interference suppression device shown in figure 6 in the region of a long shielding arm,

Fig. figure 8 shows is a plan view of part of the printed circuit board of the interference suppression device shown in figure 6, and

Fig. figure 9 shows is a perspective view of the housing wall in the region of the opening of the interference suppression device shown in figure 6. --

Page 6, ~~before~~ line 27, the paragraph beginning with "The interference suppression", insert the following title:

S.N.
5/4/07

-- DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS --

Please replace the paragraph beginning on page 6, line 27, with the following rewritten paragraph:

-- The interference suppression devices illustrated in the figures have a housing 1 made of sheet metal for an electronic appliance, which has an opening 3 at a lateral housing wall 2. A printed circuit board 5, which rests on elevated embossed areas 6 of the base 7 of the housing 1, is arranged in the housing interior 4. The printed circuit board 5 bears an electronic circuit 33 (~~not shown~~) with which contact can be made from the outside via plug elements 8, 8' and which is fed low-frequency signals via the plug elements 8, 8'. --